

itcoprime™-Red **Red Oxide Primer**

Introduction

itcoprime™-Red, Red Oxide Primer is based on Alkyd or Modified Alkyd based resin & suitable plasticizer for Steel. This coating offers corrosion resistance & fast drying properties.

This primer acts as a preparatory or protective coating that prevents rust formation on the ferrous metal surfaces exposed to humidity and air. It can be applied directly over a rusty surface after sanding and cleaning the surface. Once it fully dries, it can be covered with most conventional topcoats.

Benefits

- Suitable for mild steel surfaces and is free from heavy metals like lead, mercury, and chromium.
- Serves as a binding medium for paint coatings.
- Can be applied over porous materials to smoothen the surface.
- Eliminates the possibility of rusty surfaces in ferrous metals.

Specifications

Tests	Unit	Specification	
Color	-	Reddish Brown	
Finish	- Smooth		
Gloss Level	-	Matt	
Component	-	Single Pack	
Viscosity (30°C) (By Ford Cup No.4)	seconds	230 - 270	
Fineness of grinding (By Hegman Gauge)	H.G	4.0 - 6.0	
Specific Gravity at 30° C	gm/cc	1.25 - 1.35	
Opacity of the product	-	Good	
Drying time			
Surface dry minutes		Max 60	
Hard dry	hours	18 - 20	
Settling (thinned @ 45 sec)	-	No hard settling	

Recommended Uses

- Suitable as undercoat for wide range of Synthetic Enamel.
- Recommended as primer for steel structures and other MS Jobs.
- Good temporary corrosion prevention for metal jobs.
- Industrial and agricultural industries for outdoor equipment, railings, gates, and structural steel work.

Packaging

20 litres MS Drum

Storage

Store containers tightly closed in a cool, dry and covered place.

Reference No: ITSC/P-000121	Issue Date: June 17, 2023	Prepared By: Pamela Lobo	Date: 17/06/2023
Revision No: 00	Revision Date: NA	Approved By : Deepali Nikam	Date: 17/06/2023

Disclaimer: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall ITS Coatings Pvt. Ltd. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ITS Coatings Pvt. Ltd. has been advised of the possibility of such damages.

Head office

G 10-11, Creative Estate N.M. Joshi Marg T: +91-22-4054 6474 F: +91-22- 4054 6400 Lower Parel (E) Mumbai 400 011, INDIA E: sales@itherm.in W: www.itscoatings.in Chennai Office T: +91-22-4054 6490 / 491

