



**iTraff™ Rapisol  
Solvent Based Traffic Paint  
Golden Yellow**

**Mixing Conditions**

Mix paint thoroughly to a uniform consistency with low speed power agitation prior to use.

If settling is observed in the drum, loosen the settled material with the help of a hand stirrer followed by a power-driven stirrer for quick homogenous mixing.

10% **Thinner 9010** could be added before application.

**Application Conditions**

- Temperature: 4.5°C - 32°C for Air, surface and material  
At least 2.8 °C above the dew point
- Relative Humidity: 85% max
- Methods: Airless and Conventional Spray
- Conventional Spray: Typical
- Airless Spray
- Thinning and cleanup: Thinning

**Surface Preparation**

Surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, loose rust, and other foreign material to ensure adequate adhesion.

The presence of concrete sealers or efflorescence of new concrete may interfere with adhesion, and should be removed by extended weathering, etching, or abrasive blasting.

Most previously painted lines may be repainted without additional surface preparation, provided the old paint is still tightly adhered to the surface. However, multiple layers of paint will eventually peel, and will require removal.

New asphalt surfaces should ideally be allowed to age several months before striping. Solvent-based paints may cause bleeding through the paint. Placing an inconspicuous test stripe to determine if the asphalt has aged sufficiently to use solvent paint is recommended. If it is necessary to paint a fresh asphalt surface, use a latex striping paint following the recommended procedures.

**Clean Up Instructions**

Clean spills and spatters immediately with Xylene or Acetone. Clean tools immediately after use with Xylene or Acetone. Follow safety recommendations when using any solvent.

**Storage & Waste Disposal**

- Shelf life of unopened material is 12 months when stored in a cool, dry and covered place with minimal agitation
- For industrial/ professional use only.
- Keep away from children.
- Proper agitation and mixing of paint is imperative to ensure proper spray consistency, application results and performance.
- Refer to the SDS sheet before use.
- Make sure lids are properly closed and resealed properly to avoid any spillage during prep work or transportation.
- Strictly comply with all local and federal regulations during storage, application and disposal of paints.

**Packaging**

- 10 litres MS Drums

**Disclaimer**

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use, handling and or from contact. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way ITS Coatings Pvt. Ltd be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damage, howsoever arising, even ITS Coatings Pvt. Ltd has been advised of the possibility of such damages

Reference No: ITSC/P-00066	Issue Date: May 16, 2016	Prepared By: Prachi Pimparkar	Date: 03/12/2018
Revision No: 01	Revision Date: December 3, 2018	Approved By: Deepali Nikam	Date: 03/12/2018