# **ITCAL™** Aluminium Paint (2 pack System)

## Introduction

**ITCAL<sup>™</sup> Aluminium Paint** is fast drying synthetic resin-based system. This paint gives a bright aluminium finish with good gloss. It can resist dry heat up to 150°C. This has good corrosion, weather & water resistance. Fully cured film creates good bond on primered surface which enables it to give excellent durability in many industrial conditions.

#### Benefits

- Gives a silver metallic look to the surface
- It is fast drying in nature

**ITSCoatings** 

## Specifications

Tests	Unit	Specification		
Description	-	Metallic finish		
Color	-	Aluminium		
Component	-	2 pack		
Viscosity of medium at 30° C (By Ford Cup No.4)	seconds	18 - 20		
Specific Gravity of medium at 30° C	gm/cc	0.85 – 0.95		
Opacity of the product	-	Good		
Drying Time at 30°C				
Surface dry (to touch)	hours	Max 5		
Tack Free	hours	4 - 5		
Hard dry	hours	8 - 9		

### **Application Properties**

Recoating	Overnight
Thinning ratio	5.0 - 7.0%
Dry Film Thickness (DFT)	Recommended 25-35 microns/coat by air assisted gun
Covering capacity	150 sq. ft per coat per litre

### **Recommended Uses**

- Valves
- **Casting Bodies**
- Filtration Systems .
- Filter Cages •
- Shutters, electric poles, grills .
- Heavy Structures & many more equipments where good corrosion with Bright Silver Finish in required.

## Packaging

20 litres MS Drum along with 2 Kgs paste

#### Storage

Store containers tightly closed in a cool, dry and covered place.

Reference No: ITSC/P-000119	Issue Date: June 17, 2023	Prepared By : Pamela Lobo	Date: 17/06/2023
Revision No: 00	Revision Date: NA	Approved By : Deepali Nikam	Date: 17/06/2023

Disclaimer: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall ITS Coatings Pvt. Ltd. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ITS Coatings Pvt. Ltd. has been advised of the possibility of such damages.

Head office G 10-11, Creative Estate N.M. Joshi Marg Lower Parel (E) Mumbai 400 011, INDIA UDYAM Reg. No: UDYAM-MH-19-0004493 CIN No: U24233MH2012PTC229437

T: +91-22- 4054 6474 F: +91-22- 4054 6400 E: sales@itherm.in W: www.itscoatings.in

Chennai Office T: +91-22-4054 6490 / 491



MSME Registered