

**iTraff™ Pro**  
**Acrylic Waterborne Traffic Paint**  
**IS: 164 Grade - Grey**

**Introduction**

**iTraff™ Pro** is an Acrylic Waterborne, fast drying Traffic Paint conforming to IS-164 specifications. The product dries to no pickup in maximum 60 minutes when properly applied under recommended conditions (refer directions for use)

**iTraff™ Pro Traffic Paint** has excellent chemical and dirt resistant which provides exceptional adhesion to concrete and asphalt surfaces.

**Some key Product Features are as follows:**

- Conforms to IS 164 specifications
- Non Flammable
- High visibility
- Ready to use
- Good wear and weathering resistance
- Suitable for direct application on asphalt and concrete roads

**Recommended Uses**

- Airport Markings
- Parking lots
- City and Municipalities Roads
- Kerb Marking
- Cross Walks
- Temporary Markings

**Mixing Conditions**

If settling is observed in the drum, loosen the settled material with the help of a hand stirrer followed by a power driven stirrer for quick homogenous mixing.

**Specifications**

Tests	Unit	Typical Values
Color	-	Grey
Gloss	-	Smooth and matt to semi-glossy
Recommended WFT / Coat	Microns	25 - 35
Volume Solid	%	Approx. 35
<b>Theoretical Coverage</b>		
@ 25 mic	Sq. mt/lit.	14.0
@ 35 mic	Sq. mt/lit.	10.0
<b>Drying Time at 30°C</b>		
Surface dry	minutes	Max 30
Hard Dry	Minutes	Max 60
<b>Over coating Interval at 30°C</b>		
Minimum	45 minutes	
Maximum	Unlimited, provided surface is dry and clean from all contamination	

**Directions For Use**

- Ensure that the road surface is clean, free from dust, oil and grease
- Heavy deposits of earlier paint or thermoplastic should be removed
- Wire brushing and water washing is recommended for removal of dust from the road surface
- The surface should be thoroughly dry and free from moisture before painting
- Surface temperature must be at least 3°C above dew point but not above 50°C
- Do not paint at temperatures below 10°C or at relative humidity over 85%
- Under cold and humid conditions the paint would require longer drying time
- Two coat application is recommended for optimum performance

**iTraff™ Pro  
Acrylic Waterborne Traffic Paint  
IS: 164 Grade - Grey**

**Application Conditions**

**Brush**

Suitable for application by brush without any appreciable drag on the brush at Room temperature (21-38°C)

**Air Spray**

Nozzle Orifice: 1.5 – 3.0 mm  
Nozzle Pressure: 0.3 – 0.4 Mpa

**Airless Spray**

Nozzle Orifice: 0.33 – 0.49 mm  
Nozzle Pressure: 12 - 15 Mpa

**Note:** Municipal or Potable water may be used as thinner between 5 – 30 % only if require.

**ITS Coatings** recommends application using **Graco® Airless Spray Equipments** for best results

**Clean Up Instructions**

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits

**Packaging**

- 20 litres Plastic Pails

**Storage & Waste Disposal**

- A minimum shelf life of 12 months when stored in a cool, dry and covered place
- For professional use only.
- Keep water-based paints from freezing.
- Keep away from children.
- Proper agitation and mixing of paint is imperative to ensure proper spray consistency, application results and performance.
- Make sure lids are properly closed and resealed properly to avoid any spillage during prep work or transportation.
- Strictly comply with all local and federal regulations during storage, application and disposal of paints.

**Disclaimer**

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use, handling and or from contact . Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way ITS Coatings Pvt. Ltd be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damage, howsoever arising, even ITS Coatings Pvt. Ltd has been advised of the possibility of such damages

Reference No: ITSC/P-00085	Issue Date: February 28, 2018	Prepared By: Shruti Shroff	Date: 28/02/2018
Revision No: 00	Revision Date: NA	Approved By: Deepali Nikam	Date: 28/02/2018