

iTraff™ Seal Anti Carbonation Paint

Description

iTraff™ Seal Anti Carbonation Paint is a 100% acrylic emulsion based, heat insulating, waterproofing exterior water-based paint.

iTraff™ Seal Anti Carbonation Paint has been formulated to confer long term protective and decorative properties to concrete and masonry surfaces. The micro-porous structure of the coating acts as a barrier to the ingress of Chlorides and Carbon Dioxide and other acid gases but allows the passage of water vapour from the substrate. The elastomeric nature of Anti-Carb ensures good crack bridging properties, in case of structural movement.

Benefits

- Protects external surfaces against water seepage and similar environmental attacks
- Provides durable and long-lasting finish to the external surface
- Can withstand extreme climatic changes like heavy rainfall, high humidity and heat

Advantages

- Single pack Matt Finish paint and easy to apply
- Protects substrate from carbonation
- Excellent UV and weather resistance
- Water based and non-toxic
- Elastic nature with crack bridging properties
- Protects the structures from water leakages or dampness
- Carbon Dioxide Diffusion Resistance
- Prevents rise in internal temperature
- Prevents formation of fungi and algae hence, exteriors look freshly painted for years
- Has a fairly good resistance to abrasion due to normal wear and tear
- Does not require a priming coat, thus eliminates additional expenses and saves time

Typical Properties

Tests	Unit	Typical Properties
Color	-	White, Golden yellow and Black
Odor	-	Slight acrylic odour
pH	-	7.0 to 10.00
Viscosity at 30°C (By Brookfield)	KU	90.0 – 120.0
Volume Solid	%	58 ± 3
Carbon Dioxide permeability	g (m ² .d)	< 5.0
Diffusion Resistance against Carbon Dioxide: Equivalent air layer thickness	Meter	> 50
DFT	Microns	200- 225 Microns (For minimum 2 coats)
*Coverages	Sq. mt/lit.	2.6 – 2.9
Solvent	-	Water
Drying Time		
Touch Dry	Minutes	Max. 30
Hard Dry	Hours	8 to 12
Full Cure	Days	5
Overcoating Interval	-	Min. Overnight

Note: *The coverage of this product will vary considerably according to the roughness and porosity of the surface.

Disclaimer: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall ITS Coatings Pvt. Ltd. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ITS Coatings Pvt. Ltd. has been advised of the possibility of such damages.

iTraff™ Seal Anti Carbonation Paint**Applications**

- For new and previously painted exterior masonry, plaster, RCC and building boards surfaces
- All types of concrete structural including Building exterior, bridges, infrastructure project jobs and coastal installations.

Packaging

20 litre HDPE pails

Storage & Shelf Life

12 months when stored in a cool & dry place; away from direct sunlight, in original sealed packing

Reference No: ITSC/A-000001	Issue Date: November 22, 2024	Prepared By: Samiksha Mulik	Date: 16/09/2025
Revision No: 01	Revision Date: September 16, 2025	Approved By: Deepali Nikam	Date: 16/09/2025

Disclaimer: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall ITS Coatings Pvt. Ltd. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ITS Coatings Pvt. Ltd. has been advised of the possibility of such damages.

Head office

G 10-11, Creative Estate
N.M. Joshi Marg
Lower Parel (E)
Mumbai 400 011, INDIA
UDYAM Reg. No: UDYAM-MH-19-0004493

T: +91-22- 4054 6474
F: +91-22- 4054 6400
E: sales@itherm.in
W: www.itscoatings.in
CIN No: U24233MH2012PTC229437

Chennai Office

T: +91-22-4054 6490 / 491

MSME Registered